

signia

Life sounds brilliant.

CROS Pure[®] Charge&Go Nx

Technical Data



CROS Pure Charge&Go Nx | Features and Accessories

Style Specific Features

Ingress Protection Rating	IP68
Nanocoated housing	●
RoHS	Yes

Battery Specifications

Battery type	Li-ion
Battery voltage	1.25 V
Battery current drain	1.4 mA
Battery runtime	up to 21 h
Inductive Charger	mandatory

Technical Data

IRIL IEC 60118-13:2016 Ed. 4.0

700-960 MHz (rating)	user
1400-2000 MHz (rating)	user
2000-2700 MHz (rating)	user

ANSI C63.19-2011

800-950 MHz (rating)	M4
1600-2500 MHz (rating)	M4

Field strength magnetic link

EN300330 short range device	-22.0 dB μ A/m @ 10 m
RSS 210, issue 9	7.2 dB μ V/m @ 30 m
Sending frequency	3.28 MHz
Transmission range	18 cm

Standards

Additional information

- ▶ The current consumption is measured in normal operating mode (audio link using e2e® wireless 3.0). Due to the settling behaviour of hearing instruments, the battery current is measured 3 minutes after turning on.
- ▶ The battery runtime is based on the given current consumption. The actual battery runtime is determined by battery quality, usage and activated feature set.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice.

The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

Legal Manufacturer

Sivantos, Inc.
10 Constitution Avenue
Piscataway, NJ 08854
Phone: (800) 766-4500
Fax: (732) 562-6696
www.sivantos.com

Copyright © 2019 Signia GmbH. All rights reserved.

2/19 1.0 SI/19003-19

signiausa.com



Warning

Choking hazard posed by small parts.

- ▶ This instrument is not intended for the fitting of infants, children under 3 years and persons of mental incapacity.